



**Product Specifications**

**Benefits**

- ▶ 9U 24" LCD display panel
- ▶ 1920 x 1200 **WUXGA** native resolution / 16.7M colors
- ▶ HDMI 1.4 + DVI-D + VGA video input
- ▶ PIP Sub-screen & PBP Dual-screen viewing efficiency

**Options**

- DP 1.0 + HDMI 2.0 + Audio input & output
- Composite + Audio IN
- 3G / HD / SD-SDI Broadcast-grade input
- MCS Multi display OSD controller
- MIL-type or lockable connector
- DC power : 12V / 24V / 48V / 110V / 125V / 250V
- Touchscreen : Resistive 1-pt

Video	
Video input	HDMI 1.4 + DVI-D single link + VGA

LCD Panel	
Panel size ( diagonal )	24.1"
Native resolution	1920 x 1200
Brightness ( cd/m <sup>2</sup> )	300
Contrast ratio ( typ. )	1000 : 1
Colors	16.7 M
Viewing angle ( L/R/U/D )	89/89/89/89
Response time ( ms )	14
Dot pitch ( mm )	0.27
Display area ( mm )	518.4H x 324V
Surface treatment	Anti-glare, Hard-coating
Surface hardness	3H
Backlight type	LED
MTBF (hrs)	30,000

\* All dimensions stated are subject to change if options are selected / integrated to base model part codes

Physical		
Dimensions ( W x D x H )	Product	553 x 70 x 385 mm 21.8 x 2.8 x 15.2 inch
Weight	Net	11.4 kg / 25.1 lb

Mounting	
Rackmount	9U
VESA mount	100*100 mm

Audio Option		
Input	Connector	3.5mm stereo jack
	Impedance / Power level	30kΩ / 750mV
Output	Connector	3.5mm stereo jack
	Resistance / Power level	30kΩ / 2.8V
Speaker	Dual stereo	2W x 2

Power		
Input	Auto-sensing 100 to 240VAC, 50 / 60Hz	
Consumption	Screen on	Max. 33W
	Power saving mode	Max. 2W
	Power button off	Max. 1W

Environment	
Operating temp.	0 to 55°C degree
Storage temp.	-20 to 60°C degree
Operating humidity	10~90%, non-condensing
Storage humidity	5 ~90%, non-condensing
Operating altitude	16,000 ft
Non-operating altitude	40,000 ft
Shock	10G acceleration ( 11ms duration )
Vibration	10~300Hz 0.5G RMS random vibration

Compliance	
EMC	FCC & CE
Safety	CE / LVD & UKCA
Environment	REACH & RoHS3 / WEEE

**Diagrams ( mm )**

